



Greens

**SGN 90** 

### **Enhanced Calcitic Limestone**

#### **GUARANTEED ANALYSIS**

Calcium (Ca)	37.0%
Magnesium (Mg)	0.6%
Calcium Carbonate (CaCO <sub>3</sub> )	95.0%
Magnesium Carbonate (MgCO <sub>3</sub> )	2.0%
Calcium Carbonate Equivalent (CCE)	91.0%
Effective Neutralizing Value (ENV)	90.0%
Effective Neutralizing Power (ENP) 1776 Pounds B	ENP/Ton
Effective Neutralizing Power (ENP)       1776 Pounds B         Total Neutralizing Power (TNP)	ENP/Ton 91.0%
ů	
Total Neutralizing Power (TNP)	91.0%
Total Neutralizing Power (TNP)  Relative Neutralizing Value (RNV)	91.0% 90.0%
Total Neutralizing Power (TNP)  Relative Neutralizing Value (RNV)  Moisture Content Does Not Exceed	91.0% 90.0% 1.0%

Florida: 1,978 lb of product equal to one ton of standard liming material

Derived from Calcium Carbonate F1435

#### ALSO CONTAINS NON-PLANT FOOD INGREDIENTS

2.00% Trihydroxycarboxylic Acid (from plant extracts)1.00% Non-ionic Polyol

Trihydroxycarboxylic acid as a complexing agent.

1 quart of non-ionic polyol per 200 pounds.

#### SIEVE ANALYSIS PRIOR TO PRILLING

0.2.2.2.4						
Percent Passing	4 Mesh Sieve	100%				
Percent Passing	8 Mesh Sieve	100%				
Percent Passing	10 Mesh Sieve	100%				
Percent Passing	20 Mesh Sieve	100%				
Percent Passing	40 Mesh Sieve	100%				
Percent Passing	50 Mesh Sieve	100%				
Percent Passing	60 Mesh Sieve	98%				
Percent Passing	100 Mesh Sieve	95%				
Percent Passing	200 Mesh Sieve	90%				

Meets WV Fineness classification for pulverized

#### **CONDITIONS OF SALE**

Seller warrants that products will be labeled as required under state and federal laws and that they conform to the label description. Any non-conformance must be reported in writing to Seller within Thirty (30) days after purchase as a prerequisite to maintaining any claim against Seller. Buyer agrees to inspect all products purchased immediately upon delivery. The Seller's liability under this warranty is imited in amount to the purchase price of the product. This warranty is in lieu of all other warranties, expressed or implied, including warranties of merchantability and fitness for a particular purpose. There are no warranties which extend beyond this statement.

#### APPLICATION RECOMMENDATIONS

To maintain optimum pH and growing conditions, apply 5 pounds per 1,000 ft<sup>2</sup> or 220 pounds per acre (250 kg/ha) at least twice per growing season or as needed. Soil test recommendations should be used to determine liming needs.

To adjust pH, apply 10 pounds per 1,000 ft<sup>2</sup> or 435 pounds per acre (500 kg/ha). In most soils this will raise the soil pH up to one full point. Retest and if needed, reapply at the pH adjustment rate.



#### Warning

#### **HAZARD STATEMENT(S)**

Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation.

## PRECAUTIONARY STATEMENT(S)

Keep out of reach of children. Read label before use. Avoid breathing dust. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection/ face protection. Wear protective gloves. IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTER or doctor/physician if you feel unwell. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.

### MADE IN USA



RECOMMENDED	APPLICATION RATE			
SPREADER SETTINGS (Bulk Density: 72)		1,000 ft <sup>2</sup> kg/ha)	10 lb per 1,000 ft <sup>2</sup> (500 kg/ha)	
SPREADER TYPE	Setting	Width	Setting	Width
CYCLONE	4	10	8	10
EARTHWAY	14	11	20	11
LELY	4 II	30	9 II	33
LESCO	15 or H	10	22 or L	10
ACCUPRO 2000	14	11	18	12
SCOTTS R8	K	12	R	12
SPYKER 288	3 1/2	11	7	12
VICON	22	30	35	30
Z-SPRAY	6	16	8	16

# FOR INCORPORATION - AFTER APPLICATION - WET THOROUGHLY 30 MINUTES BEFORE TILLING. WATER IN THOROUGHLY

Information regarding the contents and levels of metals in this product is available on the internet at http://www.aapfco.org/metals.htm

LOT NO:



5484 S. Old Carriage Road, Rocky Mount, NC 27803 252.937.4107 • AQUAAIDSOLUTIONS.COM

**NET WGT: 50 lb (22.68 kg)**