t 100



Super Compact

The **Vredo DZ5 Super Compact** series is an accurate and efficient range of disc seeders designed for interseeding into prepared seedbeds or existing stands of turf. At a spacing of 1 3/8", seed is placed in a V-shaped slit, at a controllable depth of 3/16" to 1" deep, directly in contact with the soil for maximum germination rate. The slits are then closed by a roller and a level surface is re-established. The **Super Compact** series includes precision calibration and a ground driven system allowing inter-seeding to be completed at speeds between 1 and 12 mph. Seed will be accurately sown at a set rate independent of ground speed. There are two different widths available to suit tractor overlap. Models can be 3-point mounted or converted to towed-mount by the addition of an optional trail kit.



HIGHLIGHTS

- Industry leading germination rate
- Minimal surface disruption no clean up needed
- Proper seed to soil contact to maximize germination
- Each disc is independently suspended allowing continuous disc to soil penetration over undulating ground

Visit AQUAAIDSOLUTIONS.com for additional **Vredo Super Compact** pictures and videos.

Specifications

	DZ5 100	DZ5 140 / 140T		DZ5 180 / 180T		DZ5 220 / 220T	
Working Width	37"	55"		72"		88"	
Transport Width	46"	62"		79"		95	
Weight (approx)	1,191 lb	1,528 lb	1,980 lb	1,865 lb	2,317 lb	2,205 lb	2,657 lb
Recommended No. of Weights	10 (44 lb per wgt)	14 (44 lb per wgt)		18 (44 lb per wgt)		22 (44 lb per wgt)	
Weight With Recommended Weights	1,632 lb	2,145 lb	2,597 lb	2,659 lb	3,111 lb	3,175 lb	3,627 lb
Sowing Depth	3/16" - 1"						
Row Spacing	1 3/8"						
Disc Diameter	9 7/8"						
No. of Disc Sets	27	40		52		64	
Seed Hopper Volume	5.8 cu. ft.	8.3 cu. ft.		10.7 cu. ft.		13.2 cu. ft.	
Power Requirement	45 - 50 hp	50 - 60 hp		65 - 75 hp		75 - 90 hp	

Tractor Requirement: Confirm individual tractor specification has adequate lifting capacity.