



VERDE-CAL® G

Greens

SGN 85

Enhanced Gypsum

GUARANTEED ANALYSIS

Calcium Sulfate Dihydrate (CaSO ₄ •2H ₂ O)	95.0%
Calcium (Ca)	22.5%
Sulfur (S)	19.0%
19% Combined Sulfur	

Derived from Gypsum

F1435

ALSO CONTAINS NON-PLANT FOOD INGREDIENTS

2.00%	Trihydroxycarboxylic Acid (from plant extracts)
1.00%	Non-ionic Polyol

Trihydroxycarboxylic acid as a complexing agent.
1 quart of non-ionic polyol per 200 pounds.

SIEVE ANALYSIS PRIOR TO PRILLING

100% passing	4	Mesh Sieve
98% passing	8	Mesh Sieve
97% passing	10	Mesh Sieve
90% passing	20	Mesh Sieve
75% passing	40	Mesh Sieve
67% passing	50	Mesh Sieve
60% passing	60	Mesh Sieve
50% passing	100	Mesh Sieve
40% passing	200	Mesh Sieve

Information regarding the contents and levels of metals in this product is available on the internet at <http://www.aapfco.org/metals.htm>

CONDITIONS OF SALE

Seller warrants that products will be labeled as required under state and federal laws and that they conform to the label description. Any non-conformance must be reported in writing to Seller within Thirty (30) days after purchase as a prerequisite to maintaining any claim against Seller. Buyer agrees to inspect all products purchased immediately upon delivery. The Seller's liability under this warranty is limited in amount to the purchase price of the product. This warranty is in lieu of all other warranties, expressed or implied, including warranties of merchantability and fitness for a particular purpose. There are no warranties which extend beyond this statement.

APPLICATION RECOMMENDATIONS

For continued optimum growing conditions, apply pounds per 1,000 ft² or 220 pounds per acre (250 kg/ha) at 30 day intervals throughout the growing season or as needed. Soil test recommendations should be followed.

To correct high sodium or magnesium levels or to loosen clay soils, apply 10 pounds per 1,000 ft² or 435 pounds per acre (500 kg/ha) once or twice per growing season. A follow-up soil test is recommended and if needed, reapply at optimum growing conditions rate.

To correct high sodium levels on Greens and Tees when using effluent water, apply 8 pounds per 1,000 ft² (400 kg/ha) at 30 day intervals throughout the growing season or as needed.



Warning

HAZARD STATEMENT(S)

Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation.


PRECAUTIONARY STATEMENT(S)

Keep out of reach of children. Read label before use. Avoid breathing dust. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection/ face protection. Wear protective gloves. IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTER or doctor/physician if you feel unwell. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.

RECOMMENDED SPREADER SETTINGS (Bulk Density: 72)	APPLICATION RATE			
	5 lb per 1,000 ft ² (250 kg/ha)		10 lb per 1,000 ft ² (500 kg/ha)	
SPREADER TYPE	Setting	Width	Setting	Width
CYCLONE	4	10	8	10
EARTHWAY	14	11	20	11
LELY	4 II	30	9 II	33
LESCO	15 or H	10	22 or L	10
ACCUPRO 2000	14	11	18	12
SCOTTS R8	K	12	R	12
SPYKER 288	3 1/2	11	7	11
VICON	22	30	35	30
Z-SPRAY	6	16	8	16

DO NOT APPLY NEAR WATER, STORM DRAINS, OR DRAINAGE DITCHES. DO NOT APPLY IF HEAVY RAIN IS EXPECTED. APPLY THIS PRODUCT ONLY TO YOUR LAWN/GARDEN, AND SWEEP ANY PRODUCT THAT LANDS ON THE DRIVEWAY, SIDEWALK, OR STREET, BACK ONTO YOUR LAWN/GARDEN. WATER IN THOROUGHLY.

LOT NO:



MADE IN USA



5484 S. Old Carriage Road, Rocky Mount, NC 27803
252.937.4107 • AQUAAIDSOLUTIONS.COM

NET WGT: 50 lb (22.68 kg)