



VERDE-CAL[®]

Coarse

SGN 210

Enhanced Calcitic Limestone

GUARANTEED ANALYSIS

Calcium (Ca)	37.0%
Magnesium (Mg)	0.6%
Calcium Carbonate (CaCO ₃)	95.0%
Magnesium Carbonate (MgCO ₃)	2.0%
Calcium Carbonate Equivalent (CCE)	91.0%
Effective Neutralizing Value (ENV)	90.0%
Effective Neutralizing Power (ENP)	1776 Pounds ENP/Ton
Total Neutralizing Power (TNP)	91.0%
Relative Neutralizing Value (RNV)	90.0%
Moisture Content Does Not Exceed	1.0%
OK ECCE	89.9%
Oregon Lime Score	90.0

Florida: 1,978 lb of product equal to one ton of standard liming material

Derived from Calcium Carbonate

F1435

ALSO CONTAINS NON-PLANT FOOD INGREDIENTS

2.00%	Trihydroxycarboxylic Acid (from plant extracts)
1.00%	Non-ionic Polyol

Trihydroxycarboxylic acid as a complexing agent.
1 quart of non-ionic polyol per 200 pounds.

SIEVE ANALYSIS PRIOR TO PRILLING

Percent Passing	4 Mesh Sieve	100%
Percent Passing	8 Mesh Sieve	100%
Percent Passing	10 Mesh Sieve	100%
Percent Passing	20 Mesh Sieve	100%
Percent Passing	40 Mesh Sieve	100%
Percent Passing	50 Mesh Sieve	100%
Percent Passing	60 Mesh Sieve	98%
Percent Passing	100 Mesh Sieve	95%
Percent Passing	200 Mesh Sieve	90%

Meets WV Fineness classification for pulverized

CONDITIONS OF SALE

Seller warrants that products will be labeled as required under state and federal laws and that they conform to the label description. Any non-conformance must be reported in writing to Seller within Thirty (30) days after purchase as a prerequisite to maintaining any claim against Seller. Buyer agrees to inspect all products purchased immediately upon delivery. The Seller's liability under this warranty is limited in amount to the purchase price of the product. This warranty is in lieu of all other warranties, expressed or implied, including warranties of merchantability and fitness for a particular purpose. There are no warranties which extend beyond this statement.

NET WGT: 50 lb (22.68 kg)

APPLICATION RECOMMENDATIONS

To maintain optimum pH and growing conditions, apply 5 pounds per 1,000 ft² or 220 pounds per acre (250 kg/ha) at least twice per growing season or as needed. Soil test recommendations should be used to determine liming needs.

To adjust pH, apply 10 pounds per 1,000 ft² or 435 pounds per acre (500 kg/ha). In most soils this will raise the soil pH up to one full point. Retest and if needed, reapply at the pH adjustment rate.



Warning

HAZARD STATEMENT(S)

Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation.

PRECAUTIONARY STATEMENT(S)

Keep out of reach of children. Read label before use. Avoid breathing dust. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection/ face protection. Wear protective gloves. IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTER or doctor/physician if you feel unwell. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.

MADE IN USA



RECOMMENDED SPREADER SETTINGS (Bulk Density: 70)	APPLICATION RATE			
	5 lb per 1,000 ft ² (250 kg/ha)		10 lb per 1,000 ft ² (500 kg/ha)	
SPREADER TYPE	Setting	Width	Setting	Width
CYCLONE	5 1/2	12	7 1/2	12
EARTHWAY	16	11	26	11
LELY	6 1/2 II	33	10 II	33
LESCO	17 or I	10	24 or M	10
ACCUPRO 2000	15	11	21	12
SCOTTS R8	N	12	T	12
SPYKER 288	5 1/2	12	7 1/2	12
VICON	27	32	40	32
Z-SPRAY	7	16	9	16

**FOR INCORPORATION - AFTER APPLICATION - WET THOROUGHLY
30 MINUTES BEFORE TILLING. WATER IN THOROUGHLY**

Information regarding the contents and levels of metals in this product is available on the internet at <http://www.aapfco.org/metals.htm>

LOT NO:



5484 S. Old Carriage Road, Rocky Mount, NC 27803
252.937.4107 • AQUAAIDSOLUTIONS.COM